



One

Technical specifications



Materials

Base – aluminum

Cover – PBT or aluminium

Bulb – glass or acrylic

Seals – silicone

Dimensions

Ø 8,5 x H 19,5 cm (Ø 3.3 x H 7.7 inch)

Weight

0,31 kg (0,69 lbs)

Waterproof

IP65

Country of Origin

China

Light Source

E27 low-voltage bulb

Power

<1 W, 3.7 V

Color Temperature

2200 K

Dimming

3 levels (Low > Medium > High)

Light Output

27 lm (clear) – 14 lm (smoked)

Control

Switch at the base

Battery Capacity

4000 mAh

Battery life

100–140 hours (low)

60–80 hours (medium)

30–40 hours (high)

Charging

Wireless (Qi standard) or wired (USB-C)

Charging Time

Wired up to 4 hours.

Wireless up to 6 hours with 10W adapter

Adapter (not incl)

5V 2A (10W recommended), 5V 3A (15W max)

Certifications



Radio Standards and RF Exposure

Model number:	HUMTL001XX
Radio frequency:	433
Emission frequency bands:	433 MHz
Reception frequency bands:	433 MHz
Channel bandwidth:	< 400 kHz
Possibility of choosing channels:	NO
Antenna (whether it is integrated or not):	NO
Apparent Radiated Power (PAR):	10 mW
Magnetic field level:	0.02 mT
Equivalent Isotropic Radiated Power (EIRP):	10 mW
Transmitter power:	10 m
Specific Absorption Rate (DAS):	433 MHz

One


Light measurement report



CLEAR BULB

Measurements obtained

Light output: 27 lm
CCT: 2221 K
CRI: 93
Wattage: 0,45 W
Efficiency: 60 lm/W




Clear bulb - Light Intensity distribution



SMOKED BULB

Measurements obtained

Light output: 14 lm
CCT: 2223 K
CRI: 94
Wattage: 0,45 W
Efficiency: 31 lm/W



Smoked bulb - Light Intensity distribution